

- Complies with the standard for 0.6/1 kV low voltage joints (CEI EN 50393)
- Self-extinguishing (compliant with EN 60695-2-11)
- Low smoke and toxic gas emission (compliant with CEI-20-37/2-1 and CEI 20-37/7)
- **IP68 protection level** (compliant with CEI EN 60529) tested to a depth of 10 metres with independent Intertek certification
- Double insulation
- Operating temperature: from -20 to 90 °C



# SHARK® 6801-D —●— STRAIGHT

**IP68 gel insulated joint**  
for **5 core cables** straight connection  
5 insulated crimp connectors included



**code SH6801D**

## Applications

- Permanent installation under water
- Underground installation
- Overhead installation
- Installation in cable ducts
- Temporary Installations

## Advantages

- 100% waterproof
- 100% impenetrable
- Ready for use
- Re-enterable
- No pouring of resin
- Immediate operation
- Excellent electrical insulation
- Good mechanical strength
- No expiry date

## Kit contents

- Joint
- Joint locking and insulating collars
- 5 insulated crimp connectors
- Installation instructions

| APPLICATION TABLE   |  |     |
|---------------------|--|-----|
| max Number of cores | Conductor cross section (mm <sup>2</sup> ) |     |
|                     | min  | max |
|                     | 2.5  | 6   |

*Cross sections measured using FG7 flexible cables*



OFFICIALLY  
TESTED  
INTERTEK

