

- Complies with the standard for 0.6/1 kV low voltage joints (CEI EN 50393)
- Self-extinguishing (compliant with EN 60695-2-11)
- Low smoke and toxic gas emission (compliant with CEI-20-37/2-1 and CEI 20-37/7)
- **IP68 protection level** (compliant with CEI EN 60529) tested to a depth of 10 metres with independent Intertek certification
- Double insulation
- Operating temperature: from -20 to 90 °C



SHARK® 6802-A STRAIGHT

IP68 gel insulated joint
for **5 core cables** straight connection
5 pole insulated terminal block included



code SH6802A

Applications


- Permanent installation under water
- Underground installation
- Overhead installation
- Installation in cable ducts
- Temporary Installations

Advantages

- 100% waterproof
- 100% impenetrable
- Ready for use
- Re-enterable
- No pouring of resin
- Immediate operation
- Excellent electrical insulation
- Good mechanical strength
- No expiry date

Kit contents

- Joint
- Joint locking and insulating collars
- Pre-assembled 5 pole insulated terminal block
- Allen key for tightening terminal block screws
- Installation instructions

| APPLICATION TABLE | | |
|---|--|-----|
| Max number of cores | Conductor cross section (mm ²) | |
| | min | max |
|  | 2.5 | 10 |

Cross sections measured using FG7 flexible cables



OFFICIALLY
TESTED
INTERTEK

