


- Complies with the standard for 0.6/1 kV low voltage joints (CEI EN 50393)
- Self-extinguishing (compliant with EN 60695-2-11)
- Low smoke and toxic gas emission (compliant with CEI-20-37/2-1 and CEI 20-37/7)
- **IP68 protection level** (compliant with CEI EN 60529) tested to a depth of 10 metres with independent Intertek certification
- Double insulation
- Operating temperature: from -20 to +90 °C



SHARK® 6803-A —●— STRAIGHT

IP68 gel insulated joint
for **5 core cables** straight connection
5 pole insulated terminal block included



code SH6803A

Applications

- Permanent installation under water
- Underground installation
- Overhead installation
- Installation in cable ducts
- Temporary Installations

Advantages

- 100% waterproof
- 100% impenetrable
- Ready for use
- Re-enterable
- No pouring of resin
- Immediate operation
- Excellent electrical insulation
- Good mechanical strength
- No expiry date

Kit contents

- Joint
- Joint locking and insulating collars
- Pre-assembled 5 pole insulated terminal block
- Allen key for tightening terminal block screws
- Installation instructions

APPLICATION TABLE		
max number of cores	Conductor cross section (mm ²)	
	min	max
	16	25

Cross sections measured using FG7 flexible cables

